



OIL PRIMER

OIL-BASED PRIMER FOR PROTECTING MINERAL SUBSTRATES.

DESCRIPTION

ARIOMAT OIL PRIMER is a high-solid oil that acts as a primer for the protection of mineral substrates. The product is a blend of vegetable oils and a reactive thinner. After application of the **ARIOMAT OIL PRIMER** it is recommended to finish with **ARIOMAT HARDWAX OIL 2C**. Only to be used for indoor applications.

ADVANTAGES

- Easy to apply and polish with the roller
- High penetrating power
- On a natural basis
- Low VOC content

FEATURES

- Viscosity DIN 53211 (FC4): approx. 30 seconds
- Density: approx. 1 kg/l
- VOC: < 15 g/L
(i.e. amply compliant with the EU Decopaint Directive)
- Labelling: Not labelled as dangerous good

USAGE

PREPARATION

- Sand the surface to be treated thoroughly and evenly.
- Dust should be removed as much as possible (vacuum cleaning)
- The surface must be dry, free from dust, dirt and grease. If necessary, clean with water and 20 g/l ARIOMAT-SURFACE CLEANER R.
- The temperature of the product and the surface to be treated should be between +5 and +30 degrees Celsius.
- Always wear protective plastic overshoes during treatment. This is to avoid contamination of the surface.

APPLICATION

Stir the oil well before use.

ARIOMAT OIL-PRIMER is best applied by partly rolling in the surface with a thin hair roller and then immediately after rolling in with a buffing machine until the surface feels dry to the touch. Depending on the substrate and drying conditions (temperature, air humidity, ventilation...) the surface is sufficiently dry after +/- 24 hours to apply **ARIOMAT HARDWAX-OIL 2C** (please consult technical datasheet).

USE

- Consumption strongly depends on the porosity of the mineral substrate and can vary from 40 m²/litre to 20 m²/litre.

ADDITIONAL USEFUL INFORMATION

- Dried oil residues are self-igniting. Used pads and rags should therefore be immersed in water after use.

PACKAGING

- Buckets of kg 8
- 120 kg drums

STORAGE and MAINTENANCE

- Store in a dry area, frost-free and away from direct sunlight.
- In unopened original packaging, the shelf life is at least one year³ at a temperature between 5 °C and 30 °C.



OIL PRIMER

OIL-BASED PRIMER FOR PROTECTING MINERAL SUBSTRATES.

- The shelf life of an already opened package is very limited, as the product reacts with air.

SAFETY

- See safety data sheet

IMPORTANT NOTE

All information in this document is believed to be accurate, but the accuracy or completeness thereof is not guaranteed and no warranty is given in relation thereto. We shall not be liable for any loss or damage arising from the use of the product. **Own tests must be carried out prior to each treatment.** We reserve the right to change the composition of our products and the associated technical documentation without prior notice.