

## TECHNICAL DATA SHEET



## WALL PAINT PROJECT SATIN WATER BASED

UNIVERSAL PAINT FOR INTERIOR WALLS AND CEILING  
FOR NEW BUILDINGS AND RENOVATION PROJECTS

### DESCRIPTION

**WALL PAINT PROJECT SATIN** is an all-purpose matt, water-based, opaque acrylic paint for ceilings and interior walls. Especially for large new building and renovation projects.

### APPLICATION AREAS

Prepared dry **interior walls** and ceilings, on brick, plaster, plasterboard, concrete, fiberglass, wallpaper, fibreboard, wood, ...

Also used to **repaint** old wall paint layers in good condition.

### BENEFITS

- High coverage
- Water vapour permeable
- Good washability
- Economic return
- Matt
- Low odour

### ADDRESS

Apply **WALL PAINT PROJECT SATIN** to a prepared surface in 2 coats by brush, roller or spray.

### DILUTION

**WALL PAINT PROJECT SATIN** is ready for use and can, if necessary, be diluted with 1% to maximum 10% water for spray applications.

### USE

8 - 11 m<sup>2</sup>/litre on smooth and non-absorbent surfaces.

### CONDITIONS OF APPLICATION

Ambient temperature: between 5 - 30 °C  
Relative humidity: max. 80 %  
Substrate temp: between 5 - 30 °C  
Substrate humidity: max. 10

### COMPOSITION

Binder acrylic resin  
Pigments: rutile titanium dioxide  
mineral fillers  
Solvent water

### PACKAGING

White and colours	
10 Litres	V
100 Litres	V
1,000 litres	V

### COLOURS

Available in white many colors (Ariomat code)

### CLEANING TOOLS

Immediately after use with water and, if necessary, a little household detergent.

### PHYSICAL PROPERTIES

Density: 1.45 kg/litre  
Solids content: approx. 58%  
Flashpoint > 65 °C  
Appearance dry film: Light silk gloss  
Wet scrub resistance: class 1  
DIN EN 13300  
VOC (Cat.A/b): < 20 g/litre.  
Below EU limits.  
Drying time  
at 20 °C and 60% RH:  
Dust dry: 1 hour  
Can be repainted: 5 hours  
Cured: 2 days

### STORAGE and SURVEY

In unopened original packaging the shelf life is at least 1 year stored in a cool, frost-free and dry place protected from direct sunlight.

### SAFETY

Keep out of reach of children. Do not inhale the spray mist. Paint residues should only be disposed of at a container park. For further information consult the safety data sheet on:

<https://ariomat.com/t-v-verven/>

## TECHNICAL DATA SHEET



# WALL PAINT PROJECT SATIN WATER BASED

UNIVERSAL PAINT FOR INTERIOR WALLS AND CEILING  
FOR NEW BUILDINGS AND RENOVATION PROJECTS

## USAGE

**GENERAL PREPARATION OF SUBSTRATE**

**WALL PAINT PROJECT SATIN** is a one-pot system suitable on already painted surfaces in good condition and on substrates as mentioned in "application areas".

Remove loose parts and/or dust.

Clean with water and **ARIOMAT-BIOCLEANER P** and/or repair if necessary. Always rinse with water and let dry before painting.

Walls must be sufficiently dry (max 20% residual moisture) before painting.

Repairs can be done with **ARIOMAT MT FILLERLIGHT**.

Then paint with **WALL PAINT PROJECT SATIN**.

**INCLUDED**

- **Untreated substrates such as plaster, gypsum board, concrete, etc.**
  - Apply two layers of **WALL PAINT PROJECT SATIN**
- **Wall salt, salt deposits or powdered substrates and loose particles**
  - First remove dry and then fix with **ARIOMAT-WALL DUST PRIME**.
  - Apply two coats of **WALL PAINT PROJECT SATIN**.
- **Porous substrates**
  - Apply a first layer of **WALL PAINT PROJECT SATIN** with 5-10% water added.
  - Then apply one coat of **WALL PAINT PROJECT SATIN**.
- **Painted substrates with good adhesion**
  - Clean with water and **ARIOMAT BIOCLEANER P**.
  - Rinse with water and allow to dry before painting.
  - Apply two coats of **WALL PAINT PROJECT SATIN**.
- **Moss and algae growth:**
  - Brush the vegetation to be treated with diluted bleach and let it soak in for 6-number of hours.
    - Bleach 10°: 1 part bleach + 2 parts water
    - Bleach 38°: 1 part bleach + 6 parts water
  - As an environmentally friendly alternative, undiluted vinegar can be used.
  - Clean with water and **ARIOMAT BIOCLEANER P**.
  - Rinse with water and let dry before painting.
  - Apply two coats of **WALL PAINT PROJECT SATIN**.

**IMPORTANT NOTE**

All information in this document is believed to be accurate, but the accuracy or completeness thereof is not guaranteed and no warranty is given in relation thereto. We shall not be liable for any loss or damage arising from the use of the product. **Proprietary tests must be performed prior to each treatment.** We reserve the right to modify the composition of our products and the associated technical documentation without prior notice.