



MT CLEANER A

Cleaner and degreaser for various surfaces

DESCRIPTION

MT CLEANER A is an alkaline, multi-cleaner and degreaser for mineral floors, walls and ceilings coated with the MT (Micro Topping) systems.

FEATURES AND CHARACTERISTICS

- Strong cleaning
- Good degreasing
- Doesn't foam
- pH: approx. 13
- Density: approx. 1.04

APPLICATIONS

Indoor

- Mineral surfaces: e.g. **MT CALCE**, **MT ROBUSTA**, **MT ARMATO**.

APPLICATION METHOD

Method

- Because the product is irritating, gloves and protective glasses should be used. So always be very careful when using it.
- Before use, dilute **MT CLEANER A** to 1:5 with water.
- Make use of a sponge.
- Depending on the stains to be removed, this cleaning can be done in several times.

Cleaning

- Rinse the surfaces with water after use. Be very careful when rinsing **MT CALCE**.

PACKAGING

- Bottles of 1 L

STORAGE and SAFETY

- Store in a dry area and away from direct sunlight.
- In unopened original packaging, the storage time is at least 12 months at a temperature between 5 °C and 30 °C.

SAFETY

- Only use this product after taking note of the safety data sheet.
- The product is irritant. Keep out of the reach of children. Avoid eating, drinking and smoking while handling the product. In case of contact with eyes and skin, rinse immediately with plenty of water. Do not allow product to enter drains, waterways or soil.

ALVAL REMOVAL

- Only recycle empty packaging. Dispose of liquid material residues at the collection point for old paint/lacquer, dispose of dried material residues as construction and demolition waste or as municipal or household waste.

MT CLEANER
ARIOMAT
Mineral surfaces
Version date: 31/10/2023

SOBELTEC
powered by 
Rue Petit France 43
B-9600 Ronse
info@sobeltec.be

IMPORTANT ANNOUNCEMENT:

All information in this document is believed to be accurate, but its accuracy or completeness is not guaranteed and no warranty is given with respect thereto. We are not liable for any loss or any damage caused by the use of the product. **Own tests must be carried out before each treatment.** Given the versatility and diversity of the respective working conditions and materials used, we cannot cover every single case in our description. We reserve the right to change the composition of our products and the accompanying technical documentation without prior notice.