



## WOOD MAINTENANCE OIL

MAINTENANCE OIL FOR REFRESHING OILED WOOD INDOORS

### DESCRIPTION AND APPLICATION

**ARIOMAT WOOD MAINTENANCE OIL** is a single-layer maintenance oil for indoor use, to refresh and renovate oiled wood or to repair small cracks in the varnish on varnished wood.

It is recommended to treat the wear areas with **WOOD MAINTENANCE OIL** before the colour fades.

The product is the result of a unique blend of vegetable oils and hardwaxes.

### BENEFITS

- Easy to apply and buff out by roller
- On a natural basis
- Low VOC content
- Returns the original aspect of the oiled surface
- Suitable for oiled surfaces
- One component

### FEATURES

- Viscosity DIN 53211 (FC4): approx. 20-25 seconds
- Density: approx. 0.95 kg/l
- VOC: < 5 %
- Labeling: Not labeled as dangerous goods
- Pot life (A+B): +/- 2 to 4 h depending on the ambient temperature
- Colors: CLEAR only. Colours available on request

### USE

Maintenance below is always done **AFTER** observing wear zones.

#### APPLICATION

1. Work the floor with a floor polisher and a medium-abrasive pad (e.g., red pad) or with a polishing net (e.g., used 120 mesh).
2. Vacuum and clean the floor thoroughly.
3. When the floor is clean and dry, polish with **ARIOMAT MAINTENANCE OIL** well with a polisher, until the surface feels dry to the touch.  
To avoid the surface becoming sticky after treatment, it is recommended to use little product.

### DRYING TIME and CONSUMPTION

- Drying time : 6 - 8 h
- Consumption : approx. 150 m<sup>2</sup>/liter

### CLEAN

After waiting for at least one week, the floor can be cleaned with water and **ARIOMAT WOOD CLEANER N**.

### ADDITIONAL USEFUL INFO



- Dried oil residues are **self-igniting**. Used pads and rags should therefore be immersed in water after use.

### PACKAGING

#### WOOD MAINTENANCE OIL

- Bottles of 0.5L and 1L

### STORAGE and SAFETY

- Store in a dry area, frost-free and away from direct sunlight.
- In unopened original packaging, the storage time is at least 3 years at a temperature between 5 °C and 30 °C.
- Opened packages: Since the product reacts with air, its shelf life is very limited.



## WOOD MAINTENANCE OIL

MAINTENANCE OIL FOR REFRESHING OILED WOOD INDOORS

### SAFETY

- See safety data sheet

**WOOD MAINTENANCE OIL**  
ARIOMAT  
WOOD SURFACES  
Version Date: 23/05/2024



Little France Street 43  
B-9600 Ronse  
[info@sobeltec.be](mailto:info@sobeltec.be)

### IMPORTANT NOTE

All information in this document is believed to be accurate, but its accuracy or completeness is not guaranteed and no warranty is given with respect thereto. We are not liable for any loss or any damage caused by the use of the product. **Own tests should be performed before each treatment.** Given the versatility and diversity of the respective working conditions and materials used, we cannot cover every single case in our description. We reserve the right to change the composition of our products and the accompanying technical documentation without prior notice.