



WOOD AGING BASE

Waterborne stain

DESCRIPTION

WOOD AGING BASE is a stain range that creates a unique, warm and aged or smoked look effect. This range consists of non-reactive/non chemical stains which results in a more consistent look.

WOOD AGING BASE provides a nice colour depth to the treated wood, preserving its natural character. This system, as with our colour base range, is only completed by applying either the protective WOOD VARNISH or WOOD HARDWAX OIL, depending on the desired end-effect and properties.

FEATURES AND PROPERTIES

- Optimal wood penetration and saturation
- Optimal colour stability
- Easy application
- Smoked and aged look
- Available in different colours (check colour card)
- Nearly odourless
- No VOC
- Viscosity: water thin
- Density: ± 1
- Water dilutable

APPLICATION

Preparation

General: before colouring, floors must be carefully and homogenously prepared. Previous treatments from older floors must be removed completely. Protect areas that do not need to be treated.

- Sanding: According to the state of the surface.
- Cleaning: Vacuum the floor.

Application

1. Shake the product before use and regularly during application.
2. Apply generously with pistol, roller, brush, or floor polisher with a white pad.
3. Rub dry using a cloth (not necessary with floor polisher) in the direction of the grain until the colour no longer changes.
 - On rough surfaces (e.g. brushed or sandblasted oak): work the product into the grain with a brush or a cloth in circular movements.

Drying

- Drying time: depending on the drying conditions ca. 2 hours before finishing can be started. When finishing with Ariomat Wood Varnish make sure the surface is completely dry, otherwise colour transfer to the roller is possible and the end result can be negatively affected.

Consumption

- Depending on the substrate the consumption is estimated between 8 and 14 m² per litre.



WOOD AGING BASE

Waterborne stain

Finishing

After complete drying, the surface can be finished. As each specific combination will create a unique look, it is strongly advisable to carry out the necessary tests beforehand.

- **ARIOMAT WOOD VARNISH**
- **ARIOMAT WOOD HARDWAX OIL**

→ Please consult the technical data sheets of these products.

STORAGE

Store in dry conditions, in original packaging, at temperatures between 5 and 25°C.

The product is frost sensitive, use frost-free storage and transport.

Keep away from direct sunshine.

IMPORTANT NOTICE:

Our liability is limited to the product itself, its processing and application are excluded. Own tests must be carried out prior to each treatment. We reserve the right to change our products and their composition and to amend the associated technical notes without prior notice. Please ask our advisory service for the latest version of this technical note.

WOOD AGING BASE
ARIOMAT
Wood
Version date: 28/04/2025



Klein Frankrijkstraat 43
B-9600 Ronse
info@sobeltec.be