



WOOD VARNISH 2C X-MATT, MATT, SATIN

COLOURLESS AND PROTECTIVE FINISH
WITH HIGH RESISTANCE TO ABRASION AND WATER

DESCRIPTION

WOOD VARNISH 2C is a 2-component, protective and decorative varnish for various indoor wood types. **WOOD VARNISH 2C** is available in **X-MATT**, **MATT** and **SATIN**.

The extra matt varnish perfectly combines a deep appearance, accentuates the natural aspect of wood.

The product is waterborne and 2-component, 100% polyurethane based, which ensures high resistance to abrasion and water.

The **X-MATT version** has the uniqueness that no rolling stripes are visible after rolling. No overlapping. This benefit offers the possibility to perform local repairs.

FEATURES AND CHARACTERISTICS

- For indoor use
- Protects, decorates and waterproofs
- No overlapping
- Hide small scratches and defects
- No discolouration due to UV degradation
- Very easy to apply
- Durable
- Deep matt – preserves a very natural look to wood
- Transparent
- Odourless
- VOC < 20 g/L (According to Decopaint Directive 2010/75 EU)
- pH: approx. 8
- Density: ± 1
- Solvent: water

USE

For practically all types of wood. As wood is a natural product, testing is always recommended to ensure the suitability of this product on the chosen substrate.

Indoors only.

Furniture, doors, window frames, parquet, panelling, table tops, kitchens, stairs and balustrades, boards, etc.

Recommended use:

- directly on the wood
- or on both **ARIOMAT WOOD COLOUR BASE** and **ARIOMAT WOOD AGING BASE**

APPLICATION

PREPARATION

- The surface must be dry, free of dust, dirt and grease. Sand and/or clean according to the state of the surface and desired effect.
- Add 20% B-component (PART B) to **WOOD VARNISH 2C PART A** and stir well but MANUALLY before use.
Eg. - 1 L PART A + 200 ml PART B.
- As the pot-life of this mixture is greatly reduced, it is strongly recommended to mix small quantities. This mixture should be processed within 1 hour.



WOOD VARNISH 2C X-MATT, MATT, SATIN

COLOURLESS AND PROTECTIVE FINISH WITH HIGH RESISTANCE TO ABRASION AND WATER

APPLICATION

- Apply **ARIOMAT WOOD COLOUR BASE** or **ARIOMAT WOOD AGING BASE** according to the technical data sheet if pre-colouring is desired.
- By roller or brush:
 - Apply two to three thin coats of **WOOD VARNISH 2C** with a roller (short mohair roller) or brush. The recommended amount is three coats. After two coats, denib or lightly sand (150-grit paper or finer) to make the surface extra smooth if necessary.
 - Waiting time between coats: 3-5 u.
 - First coat: Drying time: approx. 1h, consumption max: 130 g/m²
 - Second coat: Drying time: approx. 2-3h, consumption max 100 g/m²
 - Third coat: Drying time: approx. 2-3h, consumption max 100 g/m²
 - Clean tools with : Water

Drying times above are averages, which can vary under different circumstances. Always wait until the previous coat is sufficiently dry.

- By spray:
 - First add PART B as described above and then dilute the product with water up to 20% if necessary. Example of maximum dilution: 800 gr WOOD VARNISH 2C + 200 gr water.
 - The same drying times as with the roller are recommended.

STORAGE

- Store in a dry place, in the original packaging, at a temperature between 5 and 25°C.
- The product is frost-sensitive, use frost-free storage and transport.
- Keep away from direct sunlight.

SAFETY

Consult the safety data sheet available on www.ariomat.com before use.

WOOD VARNISH 2C
ARIOMAT
Wood
Version: 28/04/2025

SOBELTEC
powered by 
Klein Frankrijkstraat 43
B-9600 Ronse
info@sobeltec.be

IMPORTANT NOTICE:

Our liability is limited to the product itself, its processing and application are excluded. Own tests must be carried out prior to any treatment. We reserve the right to change our products and their composition and to amend the corresponding technical notes without prior notice. Please ask our advisory service for the latest version of this technical note.